

## Installation Instructions

For 540 Smoothwall Connectors





7645 Henry Clay Blvd. Liverpool, NY 13088 Support Tel: +1 315-431-7100 Inside US: 1-888-201-6073



Installation Instructions

For 540 Smoothwall Connectors



## Step #2: Install



Slide marking guide onto cable until it bottoms.



Mark cable jacket (using pen or marker) at end of cable marking guide.



Use alcohol wipe to clean inner and outer conductors thoroughly.



Twist connector onto cable until it covers the alignment mark.

## Step #3: Compress

| Connector | Frameset Insert |
|-----------|-----------------|
| DIN       | A               |
| RA        | A               |
| Ν         | В               |
| MDM       | С               |



Insert A Insert **B** Insert C Refer to chart to select proper insert for connector type.



Select proper insert for connector. Pull/push back the insert to allow connector/ cable to lay flat in frame.



Make sure connector is fully seated. Press HCG tool trigger until gun cycles. Do not pull or push on tool during compression.



When fully compressed, connector will move away from alignment mark.

## Step #4: Torque



When using the torque wrench, make sure the mating connector is supported by an adjustable wrench.

| Series | Torque (in. lbs.) | Hex Nut Size |
|--------|-------------------|--------------|
| Ν      | 14 (1.2 ft-lbs)   | 3/4″         |
| DIN    | 216 (18 ft-lbs)   | 1-1/4"       |
| MDM    | 96 (8 ft-lbs)     | 7/8″         |
|        |                   |              |

Use proper torque based on the type of interface.





Scan for install video

Cable preparation guide

Compare to picture to determine if correct cable prep was performed. (For reference only)



10-01-2013 13261-01 revC

7645 Henry Clay Blvd. Liverpool, NY 13088

Support Tel: +1 315-431-7100 Inside US: 1-888-201-6073