

UXP-NF-78



UXP-NF-78 DATA SHEET

N Female Connector for 7/8" Annular Cables

| Mechanical | Specification | Comment |
|---|--|---|
| Pull Force Combined | > 350 lbs 1.56 kN | Cable limited |
| Cable/Connector Torque | 16 ft-lbs 21.7 N-m | Cable limited |
| Interface Durability | 50 Cycles | |
| Electrical | Specification | Comment |
| Frequency Range | DC to 5 GHz | |
| Impedance | 50Ω Nominal | |
| Average Return Loss (VSWR) DTF | > -40dB (1.02) 0-1 GHz, > -36dB (1.03) 1-2 GHz, > -32dB (1.05) 2-4 GHz, -28dB (1.08) 4-5 GHz | As per Anatel 75 |
| Insertion Loss | < .1√F(GHz) | |
| 3rd Order IMD | -153 dBc minimum, -160 dBc typical | As per IEC 62037-2, -3 |
| Voltage Withstand | > 2.5 kV | |
| Shielding Effectiveness | < -120dB | 0-1 GHz |
| Insulation Resistance | 5GΩ initial, 200MΩ after conditioning | |
| Environmental | Specification | Comment |
| Operating Temperature/Storage Temperature | -55°C to +85°C / -55°C to +85°C | |
| Interface Moisture | No leakage, mated or unmated > 1.0 Bar | |
| Moisture Ingress | No leakage | ANSI/SCTE60 2004, IP-67, IP-68, IEC 60529 |
| Corrosion Resistance | 1000 Hours | |
| H.A.L.T. | 40 Hours | |
| General | Specification | Comment |
| Cable Supported | Andrew AVA5-50, Andrew LDF5-50, Andrew AL5-50, RFS LCF78-50, Draka RFA78, Leoni 7/8"R, Eupen EC5-50, LS/Superior Essex LHF 22D, LS/Superior Essex LHF-22DU, LS/Superior Essex HFC 22D, LS/Superior Essex HFAC 22D, Hansen 7/8" | |
| Weight | 0.514 lbs. 233.1g | |
| WPS Weather Protection | | |
| Length | 2.850" 72.4mm | |
| Outer Diameter | 1.490" 26.4mm | |
| Hex Width | 1.375" 35mm | |
| Tools | Specification | Comment |
| Cable Preparation | SP-78 | |
| Connector Compression | HCG-FRAMESET-78, HCG-CC | |
| Torque Wrench | Adjustable Wrench | |