UXP-4MT-78



UXP-4MT-78 DATA SHEET

4.3–10 Male Connector for 7/8” Cables

Mechanical	Specification	Comment
Pull Force Combined	> 350 lbs | 1.56 kN	Cable limited
Cable/Connector Torque	16 ft-lbs | 21.69 N-m	Cable limited
Interface Durability	500 Cycles	

Electrical	Specification	Comment
Frequency Range	DC to 6 GHz	
Impedance	50Ω Nominal	
Average Return Loss (VSWR) DTF	> –40dB (1.02) 0–1 GHz, > –36dB (1.03) 1–2 GHz, > –32dB (1.05) 2–4 GHz, –28dB (1.08) 4–6 GHz	As per Anatel 75
Insertion Loss	< .1√F(GHz)	
3rd Order IMD	–153 dBc minimum, –160 dBc typical	As per IEC 62037-2, -3
Voltage Withstand	> 3.0 kV	
Shielding Effectiveness	< –120dB	0–1 GHz
Insulation Resistance	10GΩ initial, 100MΩ after conditioning	

Environmental	Specification	Comment
Operating Temperature/Storage Temperature	–55°C to +85°C / –55°C to +85°C	
Interface Moisture	No leakage, mated or unmated > 1.0 Bar	
Moisture Ingress	No leakage	ANSI/SCTE60 2004, IP-67, IP-68, IEC 60529
Corrosion Resistance	1000 Hours	
H.A.L.T.	40 Hours	

General	Specification	Comment
Cable Supported	Andrew AVA5-50, Andrew LDF5-50, Andrew AL5-50, RFS LCF78-50, Draka RFA78, Leoni 7/8”R, Eupen EC5-50, LS/Superior Essex LHF 22D, LS/Superior Essex LHF-22DU, LS/Superior Essex HFC 22D, LS/Superior Essex HFAC 22D, Hansen 7/8”	
Weight	.576 lbs | 261.3 g	
WPS Weather Protection		
Length	3.330 in | 84.6 mm , 2.810 in | 71.4 mm	
Outer Diameter	1.490 in | 37.8 mm	
Hex Width	.88 in | 22 mm	

Tools	Specification	Comment
Cable Preparation	SP-78	
Connector Compression	HCG-FRAMESET-78, HCG-CC	
Torque Wrench	TQ-78-F8	8 ft-lbs | 10.8 N-m

JMA WIRELESS

www.jmawireless.com
+1 315-431-7100
customerservice@jmawireless.com

LTE 4DVANCED

RoHS 2002/95/EC

Rev A
5/7/2018